

# 深圳市康华尔电子有限公司

TEL:0755-27838351

QQ:632862232

www.konuaer.com

## 型号命名 PART NUMBERING

### 高频滤波器MHz Ceramic Filter

LT CA 10.7M A5 A10 U A00 - B0

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ①产品类别product type
- ②结构、尺寸structure & size  
T: 三单元DIP型 three units DIP  
S: 低背型DIP型low-profile DIP  
C、CA、CV、CS、CE: SMD型SMD type  
普通DIP型common DIP type: 省略abbreviation
- ③标称中心频率nominal center frequency  
单位为MHz (二到四位数字加M表示) 2 to 4 digit numerals plus M, the unit is MHz
- ④类型  
带宽band width
- ⑤特性  
L: 低背型low-profile type  
A10: 低损耗型low-loss type  
LA10: 低背、低损耗型low-profile/low-loss type
- ⑥中心频率允许偏差center frequency tolerance  
U:  $\pm 30$  kHz; H:  $\pm 25$  kHz; K:  $\pm 20$  kHz; V:  $\pm 15$  kHz; J:  $\pm 10$  kHz
- ⑦特殊规格individual specification
- ⑧包装packaging

### 高频鉴频器MHz Ceramic Discriminator

JT CV 10.7M G 001 A U A00 - B0

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ①产品类别product type
- ②结构structure  
CV: SMD型  
DIP: 省略abbreviation
- ③标称中心频率nominal center frequency  
单位为MHz (二到四位数字加M表示) 2 to 4 digit numerals plus M, the unit is MHz
- ④类型type
- ⑤序列号serial No  
与IC型号有关 (一到三位数字表示) related with IC, 1 to 3 digit numerals
- ⑥振荡模式oscillating mode  
A: 厚度伸缩模式thickness expander mode  
S: 厚度剪切模式thickness shear mode
- ⑦中心频率允许偏差center frequency tolerance  
U:  $\pm 30$  kHz; H:  $\pm 25$  kHz; K:  $\pm 20$  kHz
- ⑧特殊规格individual specification
- ⑨包装packaging

### 高频陷波器MHz Ceramic Trap

XT C 10.7M T E B00 - B0

① ② ③ ④ ⑤ ⑥ ⑦

- ①产品类别product type
- ②结构structure  
C: SMD型SMD type  
DIP: 省略abbreviation
- ③标称中心频率nominal center frequency  
二到四位数字加M表示2 to 4 digit numerals plus M
- ④类型type  
A, J: 单吸收, 二端single trap, two terminals  
B, C: 单吸收, 三端single trap, three terminals  
W: 双吸收, 三端double traps, three terminals  
T: 三吸收, 三端triple traps, three terminals
- ⑤电感inductance  
E:  $5.6 \mu\text{H}$ ; G:  $8.2 \mu\text{H}$ ; L:  $15 \mu\text{H}$
- ⑥特殊规格individual specification
- ⑦包装packaging

